



Titebond Original Wood Glue

Product # 15005066

DESCRIPTION

Titebond Original Wood Glue is the industry standard for woodworking. With a strong initial tack and fast set speed to reduce clamp time, this glue develops a bond stronger than the wood itself. Offers excellent sandability and is unaffected by finishes.

Titebond Original can help any woodworker achieve professional-looking results. Ideal for wood, hardboard, particleboard, leather, cloth, and most other porous materials. Titebond Original is non-toxic, easy to use, and cleans up with water.

ADVANTAGES AND BENEFITS

- Fast setting to shorten clamp time - Bonds stronger than wood - Excellent heat and solvent resistance - Excellent sandability - Unaffected by finishes - Versatile: bonds wood, hardboard, high pressure laminates and particleboard - Easy clean-up with water

TECHNICAL SPECIFICATIONS

Product #	15005066
Recommended Use	Interior, General-Use Glue
Color Before Application	Yellow
Dried Film	Translucent
Open Time	1 to 5 minutes
Viscosity	3200 cps
Volume	1 gal.
Brand	Titebond®
Features	Solvent Resistant, Fast Setting, High Heat Resistance
VOC Concentration (EPA Method 24)	10.7 grams per liter
Standards and Certifications	CARB, ASTM D-4236
Solid Content (Approx.)	46%
Base	Aliphatic Resin Emulsion
pH	4.6
Freeze/Thaw Stability	Keep From Freezing, Stable

APPLICATION

All common wood species, particleboard, MDF, plywood, and other porous materials.

IMPORTANT INFORMATION

- Conforms to ASTM D-4236 - Within the formaldehyde limits set by the California Air Resources Board (CARB)

PRODUCT PHOTOS

