



## Kleiberit 569.0 PUR Construction Glue

**Product #** 56911

### DESCRIPTION

A polyurethane-based construction adhesive with an extremely high bond strength. This moisture-curing single-component adhesive is designed to bond a variety of porous and non-porous materials.

### ADVANTAGES AND BENEFITS

- Thixotropic and stable - Excellent for gap filling - Easy application - Slightly foaming

### TECHNICAL SPECIFICATIONS

<b>Product #</b>	56911
<b>Volume</b>	310 ml
<b>Base</b>	Polyurethane
<b>Weight</b>	325 g
<b>VOC Concentration (EPA Method 24)</b>	0 grams per liter
<b>Standards and Certifications</b>	EN 204 D4, Watt 91
<b>Open Time</b>	10 to 15 minutes
<b>Finish/Color</b>	Clear Transparent
<b>Viscosity</b>	400 000 cps
<b>Brand</b>	Kleiberit
<b>Features</b>	High Heat Resistance, Non-Flammable
<b>Recommended Use</b>	Polyurethane Construction Adhesive, Bonding Porous Surface to Non-Porous Surface
<b>Foams when Drying</b>	Foams Slightly
<b>Application Temperature</b>	above 5 °C (41 °F)
<b>Solid Content (approx.)</b>	100%

### APPLICATION

Suitable for bonding: - Wood and wood-based materials - Metal - Insulating foam - Polystyrene foam - Concrete - Other mineral materials to porous substrates

### IMPORTANT INFORMATION

High resistance to water according to DIN EN 204 D4 High temperature resistance according to WATT 91 (DIN EN 14257)

## PRODUCT PHOTOS

---

